# Safety Data Sheet ULTRAFLEX LHT WHITE

Safety Data Sheet dated: 01/08/2024 - version 2

Date of first edition: 06/15/2021



### 1. IDENTIFICATION

#### **Product identifier**

Mixture identification:

Trade name: ULTRAFLEX LHT WHITE

Trade code: 9021830

Recommended use of the chemical and restrictions on use

Recommended use: Polymer modified mortar

Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico) 1144 East Newport Center Drive

33442 - Deerfield Beach - FL - USA

Responsable: RDProductSafety@mapei.com

**Emergency 24 hour numbers:** 

Phone: 954-246-8888

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

## 2. HAZARD(S) IDENTIFICATION







# Classification of the chemical

Skin corrosion, Category 1A Causes severe skin burns and eye damage.

Serious eye damage, Category 1 Causes serious eye damage.

Skin Sensitization, Category 1 May cause an allergic skin reaction.

Carcinogenicity, Category 1A May cause cancer if inhaled, in contact with skin and if swallowed.

Specific target organ toxicity following single exposure, May cause respiratory irritation.

Category 3

#### **Label elements**

#### Hazard pictograms and Signal Word



Danger

## **Hazard statements**

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.H335 May cause respiratory irritation.

H350 May cause cancer if inhaled, in contact with skin and if swallowed.

#### **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P33 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

1

Print date 01/08/2024 Production Name ULTRAFLEX LHT WHITE Page n. 1 of 9

P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P35 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

3

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P33 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

8 to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P310 Immediately call a doctor.
P312 Call a doctor if you feel unwell.

P321 Specific treatment (see supplementary instructions on this label)
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

#### Ingredient(s) with unknown acute toxicity:

None

#### Hazards not otherwise classified identified during the classification process:

None

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substances

Not Relevant

#### **Mixtures**

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

#### List of components

Qty	Name	Ident. Numb.	Classification	Registration Number
25-50 %	portland cement; cement, portland, chemicals		STOT SE 3, H335; Eye Dam. 1, H318; Skin Sens. 1, H317; Skin Corr. 1A, H314	
0.49-1 %	silica sand; quartz	CAS:14808-60-7 EC:238-878-4	7 STOT RE 1, H372; Carc. 1A, H350	

## 4. FIRST AID MEASURES

# Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Obtain medical attention if skin related symptoms persist.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation

In case of inhalation, consult a doctor immediately and show him packing or label.

## Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

## Indication of any immediate medical attention and special treatment needed

Print date 01/08/2024 Production Name ULTRAFLEX LHT WHITE Page n. 2 of 9

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

#### 5. FIRE-FIGHTING MEASURES

#### **Extinguishing media**

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

#### Unsuitable extinguishing media:

None in particular.

## Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not Relevant Oxidizing properties: Not Relevant

## Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### **6. ACCIDENTAL RELEASE MEASURES**

# Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

### Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations

Scoop into containers and seal for disposal.

Retain contaminated washing water and dispose it.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

#### Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Storage temperature: Not available

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control parameters**

#### **Community Occupational Exposure Limits (OEL)**

OEL Country Occupational Exposure Limit

Print date 01/08/2024 Production Name ULTRAFLEX LHT WHITE Page n. 3 of 9

Type

portland cement; cement, portland, chemicals CAS: 65997-15-1

OSHA Long Term: 15 mg/m3

OSHA Long Term: 5 mg/m3
ACGIH Long Term: 1 mg/m3

A4 - Not Classifiable as a Human Carcinogen; pulmonary function; respiratory

symptoms; asthma;

ACGIH Long Term: 1 mg/m3

A4 - Not Classifiable as a Human Carcinogen; pulmonary function; respiratory

symptoms; asthma

MAK AUSTRIA Long Term: 5 mg/m3 MAK SWITZERLAN Long Term: 5 mg/m3

D

silica sand; quartz CAS: 14808-60-7 ACGIH Long Term: 0.025 mg/m3

A2 - Suspected Human Carcinogen; lung cancer; pulmonary fibrosis;

ACGIH Long Term: 0.025 mg/m3

A2 - Suspected Human Carcinogen; lung cancer; pulmonary fibrosis

MAK AUSTRIA Long Term: 0.15 mg/m3
MAK SWITZERLAN Long Term: 0.15 mg/m3

D

Appropriate engineering controls: Not available

## **Individual protection measures**

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105: Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

#### Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

# Information on basic physical and chemical properties

Physical state: Solid

Appearance and colour: powder white

Odour: cement like

Odour threshold: Not Relevant

pH: Not Relevant

pH (water dispersion, 10%): 12.50

Melting point / freezing point: Not Relevant
Initial boiling point and boiling range: Not Relevant

Flash point: Not Relevant Evaporation rate: Not Relevant

Upper/lower flammability or explosive limits: Not Relevant

Vapour density: Not Relevant Vapour pressure: Not Relevant Relative density: 1.50 g/cm3 Solubility in water: dispersible Solubility in oil: Not Relevant

Partition coefficient (n-octanol/water): Not Relevant

Auto-ignition temperature: Not Relevant

Print date 01/08/2024 Production Name ULTRAFLEX LHT WHITE Page n. 4 of 9

Decomposition temperature: Not Relevant

Viscosity: Not Relevant

Explosive properties: Not Relevant Oxidizing properties: Not Relevant Solid/gas flammability: Not Relevant

#### Other information

Substance Groups relevant properties Not Relevant

Miscibility: Not Relevant Fat Solubility: Not Relevant Conductivity: Not Relevant

## 10. STABILITY AND REACTIVITY

#### Reactivity

Stable under normal conditions

#### Chemical stability

Data not available.

## Possibility of hazardous reactions

None.

#### **Conditions to avoid**

Stable under normal conditions.

## **Incompatible materials**

None in particular.

#### **Hazardous decomposition products**

None.

#### 11. TOXICOLOGICAL INFORMATION

b) skin corrosion/irritation

c) serious eye damage/irritation

#### Information on toxicological effects

## **Toxicological Information of the Preparation**

a) acute toxicity Not classified

Based on available data, the classification criteria are not met
The product is classified: Skin corrosion, Category 1A(H314)
The product is classified: Serious eye damage, Category 1(H318)

d) respiratory or skin sensitisation The product is classified: Skin Sensitization, Category 1(H317)

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity The product is classified: Carcinogenicity, Category 1A(H350)

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure The product is classified: Specific target organ toxicity following single exposure,

Category 3(H335)

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

#### Toxicological information on main components of the mixture:

silica sand; quartz a) acute toxicity LD50 Oral Rat = 500 mg/kg

## Substance(s) listed on the IARC Monographs:

silica sand; quartz Group 1

### Substance(s) listed as OSHA Carcinogen(s):

silica sand; quartz

### Substance(s) listed as NIOSH Carcinogen(s):

silica sand; quartz

## Substance(s) listed on the NTP report on Carcinogens:

silica sand; quartz

Print date 01/08/2024 Production Name ULTRAFLEX LHT WHITE Page n. 5 of 9

#### 12. ECOLOGICAL INFORMATION

#### **Toxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

#### List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

Based on available data, the classification criteria are not met

### List of Eco-Toxicological properties of the components

Component Ident. Numb. Ecotox Data

silica sand; quartz CAS: 14808-60- a) Aquatic acute toxicity: LC50 carp > 10000 mg/L 72h

7 - EINECS: 238-878-4

## Persistence and degradability

N.A.

### **Bioaccumulative potential**

N.A.

#### Mobility in soil

N.A.

#### Other adverse effects

N.A.

#### 13. DISPOSAL CONSIDERATIONS

### **Waste treatment methods**

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

#### Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

### Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

#### Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

#### 14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

#### **UN** number

DOT-UN Number: Not Applicable ADR-UN number: Not Applicable IATA-Un number: Not Applicable IMDG-Un number: Not Applicable

#### **UN proper shipping name**

DOT-Proper Shipping Name: Not Applicable ADR-Shipping Name: Not Applicable IATA-Technical name: Not Applicable IMDG-Technical name: Not Applicable

## Transport hazard class(es)

DOT-Hazard Class: Not Applicable ADR-Class: Not Applicable

Print date 01/08/2024 Production Name ULTRAFLEX LHT WHITE Page n. 6 of 9

IATA-Class: Not Applicable IMDG-Class: Not Applicable

#### **Packing group**

DOT Packing Group: Not Applicable ADR-Packing Group: Not Applicable IATA-Packing group: Not Applicable IMDG-Packing group: Not Applicable

### **Environmental hazards**

Marine pollutant: No

Environmental Pollutant: Not Applicable

DOT-RQ: No

#### Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

#### Special precautions

Department of Transportation (DOT):

Not Applicable

Road and Rail (ADR-RID):

Not Applicable

Air (IATA):

Not Applicable

Sea (IMDG):

Not Applicable

#### 15. REGULATORY INFORMATION

## **USA - Federal regulations**

### **TSCA - Toxic Substances Control Act**

All the components are listed on the TSCA inventory

#### **TSCA listed substances:**

portland cement; cement,

is listed in TSCA Section 8b

portland, chemicals

silica sand; quartz is listed in TSCA Section 8b

## **SARA - Superfund Amendments and Reauthorization Act**

**Section 302 - Extremely Hazardous Substances:** 

No substances listed

#### Section 304 - Hazardous substances:

No substances listed

#### Section 313 - Toxic chemical list:

No substances listed

# CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act Substance(s) listed under CERCLA:

No substances listed

#### CAA - Clean Air Act

# **CAA listed substances:**

No substances listed

## **CWA - Clean Water Act**

#### **CWA listed substances:**

No substances listed

## **USA - State specific regulations**

## **California Proposition 65**

# Substance(s) listed under California Proposition 65:

silica sand; quartz Listed as carcinogen

# Massachusetts Right to know

### Substance(s) listed under Massachusetts Right to know:

portland cement; cement, portland, chemicals

silica sand; quartz

## Pennsylvania Right to know

# Substance(s) listed under Pennsylvania Right to know:

Print date 01/08/2024 Production Name ULTRAFLEX LHT WHITE Page n. 7 of 9

silica sand; quartz

#### New Jersey Right to know

### Substance(s) listed under New Jersey Right to know:

portland cement; cement, portland, chemicals

silica sand; quartz

## **Canada - Federal regulations**

#### **DSL - Domestic Substances List**

All the substances are listed in the DSL.

#### **NDSL - Non Domestic Substances List**

This product complies with NDSL inventory

#### **NPRI - National Pollutant Release Inventory**

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

#### 16. OTHER INFORMATION

Safety Data Sheet dated: 1/8/2024 - version 2 **Additional classification information** 

NFPA Health: 2 = Moderate

NFPA Flammability: 0 = Not Combustible

NFPA Reactivity: 0 = MinimalNFPA Special Risk: N.A.



Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description		
H314	Causes severe skin burns and eye damage.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H335	May cause respiratory irritation.		
H350	May cause cancer.		
H372	Causes damage to organs through prolonged or repeated exposure.		
Code	Hazard class and hazard category Description		

Code	Hazard class and hazard category	Description	
A.2/1A	Skin Corr. 1A	Skin corrosion, Category 1A	
A.3/1	Eye Dam. 1	Serious eye damage, Category 1	
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1	
A.6/1A	Carc. 1A	Carcinogenicity, Category 1A	
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3	
A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1	

## Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

01/08/2024 Production Name **ULTRAFLEX LHT WHITE** Print date Page n. 8 of 9



LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

## Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 5. FIRE-FIGHTING MEASURES
- 7. HANDLING AND STORAGE
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 16. OTHER INFORMATION

Print date 01/08/2024 Production Name ULTRAFLEX LHT WHITE Page n. 9 of 9